

IIDWay Technology Co.Ltd

PRODUCT SPECIFICATION

5.0” Semi-Reflective TFT MODULE

Part Number : GZ70201-OIF050WV

Version : 1.0

< ◇ > Preliminary Specification

< ◆ > Finally Specification

| CUSTOMER'S APPROVAL | |
|---------------------|-------|
| CUSTOMER : | |
| SIGNATURE: | DATE: |
| | |

| APPROVED BY | PM REVIEWED | PD REVIEWED | PREPARED BY |
|----------------|----------------|----------------|----------------|
| | | | |

Revision History

| Revision | Date | Originator | Detail | Remarks |
|----------|----------|------------|-----------------|---------|
| 1.0 | 20231109 | | Initial Release | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |

Table of Contents

| No. | Item | Page |
|-------|--|------|
| 1. | General Description | 4 |
| 2. | Module Parameter | 4 |
| 3. | Absolute Maximum Ratings..... | 5 |
| 4. | DC Characteristics | 5 |
| 5. | Backlight Characteristics | 5 |
| 5.1. | Backlight Characteristics..... | 5 |
| 5.2. | Backlighting circuit | 6 |
| 6. | Optical Characteristics | 7 |
| 6.1. | Optical Characteristics | 7 |
| 6.2. | Definition of Response Time | 8 |
| 6.3. | Definition of Contrast Ratio | 8 |
| 6.4. | Definition of Viewing Angles..... | 9 |
| 6.5. | Definition of Color Appearance | 9 |
| 6.6. | Definition of Surface Luminance, Uniformity and Transmittance..... | 9 |
| 7. | Block Diagram and Power Supply..... | 10 |
| 8. | Interface Pins Definition | 11 |
| 9. | AC Characteristics..... | 13 |
| 9.1. | AC Timing characteristics..... | 13 |
| 9.2. | Display Timing characteristics..... | 14 |
| 9.3. | Power ON/Off Sequence | 15 |
| 10. | Quality Assurance | 16 |
| 10.1. | Purpose..... | 16 |
| 10.2. | Standard for Quality Test | 16 |
| 10.3. | Nonconforming Analysis & Disposition | 16 |
| 10.4. | Agreement Items..... | 16 |
| 10.5. | Standard of the Product Visual Inspection..... | 16 |
| 10.6. | Inspection Specification | 17 |
| 10.7. | Classification of Defects..... | 21 |
| 10.8. | Identification/marketing criteria | 21 |
| 10.9. | Packing | 21 |
| 11. | Reliability Specification..... | 22 |
| 12. | Precautions and Warranty..... | 23 |
| 12.1. | Safety | 23 |
| 12.2. | Handling | 23 |
| 12.3. | Storage..... | 23 |
| 12.4. | Metal Pin (Apply to Products with Metal Pins)..... | 23 |
| 12.5. | Operation | 24 |
| 12.6. | Static Electricity..... | 24 |
| 12.7. | Limited Warranty | 24 |
| 13. | Packaging..... | 25 |
| 14. | Outline Drawing..... | 26 |

1. General Description

The specification is a transmissive type color active matrix liquid crystal display (LCD) which uses amorphous thin film transistor (TFT) as switching devices. This product is composed of a TFT-LCD panel, driver Ics and a backlight unit.

2. Module Parameter

| Features | Details | Unit |
|--------------------------------|--|------------|
| Display Size(Diagonal) | 5.0" | |
| LCD type | Semi-Reflective TFT | |
| Display Mode | Normally White/Translucent/ | |
| Resolution | 800 RGB x 480 | Pixels |
| View Direction | Free | Best Image |
| Gray Scale Inversion Direction | / | |
| Module Outline | 120.7 (H) x 75.8(V) x 2.85(T) (Note1) | mm |
| Active Area | 108 (H) x 64.8(V) | mm |
| Pixel Size | 135 (H) x 135(V) | um |
| Pixel Arrangement | R.G.B Vertical Stripe | |
| Polarizer Surface Treatment | Anti-Glare | |
| Display Colors | 16.7M | |
| Interface | 24-bit RGB interface | |
| Driver IC | JD9165A-B | - |
| With or Without Touch Panel | Without | |
| Operating Temperature | -20~70 | °C |
| Storage Temperature | -30~80 | °C |
| Weight | 105 | g |

Note 1: Exclusive hooks, posts, FFC/FPC tail etc.

CTP characteristic

| Item | CTP Description | | | | CTP PIN SYMBOL | |
|--------------------------|-----------------|------|-------------------|---------------------|----------------|--------|
| IC | ST1633i | | | | 1 | VDD |
| Interface | I2C | | | | 2 | GND |
| Operation voltage | 3.3V | | | | 3 | TP-INT |
| Interface signal voltage | 3.3V | Item | Main layer define | Thickness/materials | 4 | TP-RTS |
| Surface hardness | ≥6H | 1 | Lens | 3mm/Glass | 5 | TP-SCL |
| Operation temperature | -20°C~+70°C | 2 | Optical Glue | 0.2mm | 6 | TP-SDA |
| Storage temperature | -30°C~+80°C | 3 | sensor | 0.7mm/Glass | | |
| Strengthened Type | Chemical | 4 | | | | |
| Transmittance | ≥85% | 5 | | | | |
| Origin of coordinates | Bottom-Right | 6 | | | | |
| Resolution Ratio | 800480 | 7 | | | | |

3. Absolute Maximum Ratings

GND=0V, Ta=25°C

| Item | Symbol | Min. | Max. | Unit |
|-----------------------|------------------|------------|------------|------|
| Supply Voltage | VDD | -0.3 | 5.0 | V |
| Storage temperature | T _{STG} | -40 | +90 | °C |
| Operating temperature | T _{OP} | -30 | +85 | °C |

Note 1: If Ta below 50°C, the maximal humidity is 90%RH, if Ta over 50°C, absolute humidity should be less than 60%RH.

Note 2: The response time will be extremely slow when the operating temperature is around -10°C, and the back ground will become darker at high temperature operating.

4. DC Characteristics

| Item | Symbol | Min. | Typ. | Max. | Unit |
|---------------------------------------|-------------------|----------|------|----------|------|
| Supply Voltage | VDD | 3.0 | 3.3 | 3.6 | V |
| | AVDD | - | - | - | V |
| | VGH | 15 | 18 | 20 | V |
| | VGL | -12 | -8 | -6 | V |
| Digital Supply Current(Black Pattern) | I _{AVDD} | - | -- | - | mA |
| | I _{VGH} | - | 470 | - | uA |
| | I _{VGL} | - | -490 | - | uA |
| Input signal voltage | VCOM | 2.7 | 3.8 | 4.7 | V |
| Logic Low input voltage | V _{IL} | 0 | - | 0.3*DVDD | V |
| Logic High input voltage | V _{IH} | 0.7*DVDD | - | DVDD | V |

Note 1: Be sure to apply DVDD and VGL to the LCD first, and then apply VGH.

Note 2: DVDD setting should match the signals output voltage (refer to Note 3) of customer's system board.

Note 3: DCLK,HS,VS,RESET,U/D,L/R,DE,R0~R7,G0~G7,B0~B7,MODE,DITHB.

Note 4: Typical VCOM is only a reference value. It must be optimized according to each LCM. Please use VR and base on below application circuit.

5. Backlight Characteristics


5.1. Backlight Characteristics

| Item | Symbol | Condition | Min. | Typ. | Max. | Unit |
|------------------------|--|------------------------------------|-------|-------------|------|------|
| Backlight Voltage | V _{LED} | Ta=25 °C, I _F =20mA/LED | 16.8 | 18.6 | 19.2 | V |
| Backlight Current | I _{LED} | Ta=25 °C, V _F =3.2V/LED | - | 60 | - | mA |
| Power dissipation | PD | | - | 1116 | - | mW |
| Uniformity | Avg | | | 75 | - | % |
| LED working life(25°C) | - | | 20000 | 30000 | - | Hrs |
| Drive method | Constant current | | | | | |
| LED Configuration | 18 White LEDs(6 LEDs in one string and 3 groups in parallel) | | | | | |

Note1: LED life time defined as follows: The final brightness is at 50% of original brightness.

The environmental conducted under ambient air flow, at Ta=25±2 °C,60%RH±5%, I_F=20mA/LED.

5.2. Backlighting circuit



6. Optical Characteristics

6.1. Optical Characteristics

| Item | Symbol | Condition | Min. | Typ. | Max. | Unit | Note | |
|---------------------------------------|--------|--|------|-------|------|------|---|---|
| White Reflectance (with Polarizer) | Rw (%) | $\Theta=0$ Normal viewing angle | — | 12.99 | — | % | (4) Measuring with HSD polarizer · Reference Only Base on Vop=4.2V | |
| Contrast Ratio | CR | — | — | 12 | — | — | (1)(2) Base on Vop=4.2V | |
| NCS | S(%) | — | — | 109 | — | % | | |
| Response Time | ms | | | 5 | | | | |
| Viewing Angle | Hor. | Θ_L | CR>2 | — | 60 | — | — | (1)(4) Measuring with HSD polarizer · Reference Only |
| | | Θ_R | | — | 60 | — | | |
| | Ver. | Θ_U | | — | 60 | — | | |
| | | Θ_D | | — | 60 | — | | |


4.2 Optical Specification (Transmissive, w/HSD FOG+D65 light)

| Item | Symbol | Condition | Min. | Typ. | Max. | Unit | Note | |
|---|--------|--|------|-------|------|------|---|---|
| White Transmittance (with Polarizer) | Tr(%) | $\Theta=0$ Normal viewing angle | — | 0.53 | — | % | (4) Measuring with HSD polarizer · Reference Only Base on Vop=4.2V | |
| Contrast Ratio | CR | — | — | 15 | — | — | (1)(2) Base on Vop=4.2V | |
| Color Gamut | S(%) | — | — | 10 | — | % | | |
| White chromaticity (CIE1931) | Wx | — | | 0.317 | | | | |
| | Wy | | | 0.359 | | | | |
| Response Time | ms | | | 6 | | | | |
| Viewing Angle | Hor. | Θ_L | CR>2 | — | 60 | — | — | (1)(4) Measuring with HSD polarizer · Reference Only |
| | | Θ_R | | — | 60 | — | | |
| | Ver. | Θ_U | | — | 60 | — | | |
| | | Θ_D | | — | 45 | — | | |

Ta=25°C, DVDD=3.3V

6.2. Definition of Response Time

6.2.1. Normally Black Type (Negative)




Tr is the time it takes to change from non-selected stage with relative luminance 10% to selected state with relative luminance 90%;

Tf is the time it takes to change from selected state with relative luminance 90% to non-selected state with relative luminance 10%

Note: Measuring machine: LCD-5100

6.2.2. Normally White Type (Positive)



Tr is the time it takes to change from non-selected stage with relative luminance 90% to selected state with relative luminance 10%;

Tf is the time it takes to change from selected state with relative luminance 10% to non-selected state with relative luminance 90%;

Note: Measuring machine: LCD-5100 or EQUI

6.3. Definition of Contrast Ratio


Contrast is measured perpendicular to display surface in reflective and transmissive mode. The measurement condition is:

| | |
|--------------------------|--------------------------|
| Measuring Equipment | Eldim or Equivalent |
| Measuring Point Diameter | 3mm//1mm |
| Measuring Point Location | Active Area centre point |
| Test pattern | A: All Pixels white |
| | B: All Pixel black |

| | |
|------------------|---------|
| Contrast setting | Maximum |
|------------------|---------|

Definitions: CR (Contrast) = Luminance of White Pixel / Luminance of Black Pixel

6.4. Definition of Viewing Angles




Measuring machine: LCD-5100 or EQUI

6.5. Definition of Color Appearance

R,G,B and W are defined by (x, y) on the IE chromaticity diagram

NTSC=area of RGB triangle/area of NTSC triangleX100%

Measuring picture: Red, Green, Blue and White (Measuring machine: BM-7)



6.6. Definition of Surface Luminance, Uniformity and Transmittance


Using the transmissive mode measurement approach, measure the white screen luminance of the display panel and backlight.

6.6.1. Surface Luminance: $L_v = \text{average} (L_{P1}:L_{P9})$


6.6.2. Uniformity = $\text{Minimal} (L_{P1}:L_{P9}) / \text{Maximal} (L_{P1}:L_{P9}) * 100\%$

6.6.3. Transmittance = $L_v \text{ on LCD} / L_v \text{ on Backlight} * 100\%$

Note: Measuring machine: BM-7



7. Block Diagram and Power Supply



8. Interface Pins Definition

| No. | Symbol | Function | Remark |
|-----|--------|--|--------|
| 1 | VLED- | Backlight Cathode | |
| 2 | VLED+ | Backlight Anode | |
| 3 | GND | Ground | |
| 4 | VDD | Power source | |
| 5 | R0 | Red data signal | |
| 6 | R1 | Red data signal | |
| 7 | R2 | Red data signal | |
| 8 | R3 | Red data signal | |
| 9 | R4 | Red data signal | |
| 10 | R5 | Red data signal | |
| 11 | R6 | Red data signal | |
| 12 | R7 | Red data signal | |
| 13 | G0 | Green data signal | |
| 14 | G1 | Green data signal | |
| 15 | G2 | Green data signal | |
| 16 | G3 | Green data signal | |
| 17 | G4 | Green data signal | |
| 18 | G5 | Green data signal | |
| 19 | G6 | Green data signal | |
| 20 | G7 | Green data signal | |
| 21 | B0 | Blue data signal | |
| 22 | B1 | Blue data signal | |
| 23 | B2 | Blue data signal | |
| 24 | B3 | Blue data signal | |
| 25 | B4 | Blue data signal | |
| 26 | B5 | Blue data signal | |
| 27 | B6 | Blue data signal | |
| 28 | B7 | Blue data signal | |
| 29 | GND | Ground | |
| 30 | PCLK | Clock signal to sample each data | |
| 31 | DISP | Display on/off signal DISP="H" Display on DISP="L" Display off | |
| 32 | Hsync | Horizontal synchronizing signal | |
| 33 | Vsync | Vertical synchronizing signal | |
| 34 | DE | Input data enable control. | |
| 35 | NC | No connection | |
| 36 | GND | Ground | |
| 37 | TP-INT | Interrupt function of CTP | |
| 38 | TP-RTS | Reset function for CTP | |
| 39 | TP-SCL | Series CLK communication PIN of CTP | |
| 40 | TP-SDA | Series data communication PIN for CTP | |

Note 1: DE/SYNC mode select. Normally pull high.

When select DE mode, MODE="1", VS and HS must pull high.

When select SYNC mode, MODE="0", DE must be grounded.

Note 2: When input 18 bits RGB data, the two low bits of R,G and B data must be grounded.


Note 3: Data shall be latched at the falling edge of DCLK.

Note 4: Selection of scanning mode.

| Setting of scan control input | | Scanning direction |
|-------------------------------|------|---------------------------|
| U/D | L/R | |
| GND | DVDD | Up to down, left to right |
| DVDD | GND | Down to up, right to left |
| GND | GND | Up to down, right to left |
| DVDD | DVDD | Down to up, left to right |

Note 5: Definition of scanning direction.

Refer to the figure as follow:



Note 6: Global reset pin. Active low to enter reset state. Suggest to connect with and RC reset circuit for stability.

Normally pull high.

Note 7: Dithering function enable control, normally pull high.


When DITHB="1", Disable internal dithering function.

When DITHB="0", Enable internal dithering function.


9. AC Characteristics

9.1. AC Timing characteristics


● Horizontal timing



● Vertical timing



9.2. Display Timing characteristics



Input data /sync. parameters

| Parameter | Symbol | Spec. | | | Unit |
|------------------|-----------|-------|------|------|------|
| | | Min. | Typ. | Max. | |
| CLKIN period | T_{cph} | 14 | - | - | ns |
| CLKIN duty ratio | T_{cw} | 40 | 50 | 60 | % |
| Data setup time | T_{dsu} | 5 | - | - | ns |
| Data hold time | T_{dhd} | 5 | - | - | ns |
| VSD setup time | T_{ss} | 5 | - | - | ns |
| VSD hold time | T_{sh} | 5 | - | - | ns |
| HSD setup time | T_{ss} | 5 | - | - | ns |
| HSD hold time | T_{sh} | 5 | - | - | ns |
| DEN setup time | T_{ss} | 5 | - | - | ns |
| DEN hold time | T_{sh} | 5 | - | - | ns |


9.3. Power ON/Off Sequence

To prevent the device damage from latch up, the power ON/OFF sequence shown below must be followed.

Power ON: VDD, DGND → VDDA, AGND → V1 to V14

Power OFF: V1 to V14 → VDDA, AGND → VDD, DGND

In order to prevent ILI6122 from power ON reset fail, the rising time (t_{POR}) of the digital power supply VDD should be maintained within given specifications. The power ON/OFF timing sequence is illustrated as below:



Note: For prevent anormal operation, t_{RST} must be longer than 10us during Power ON sequence.

10. Quality Assurance

10.1.Purpose

This standard for Quality Assurance assures the quality of LCD module products supplied to customer.

10.2.Standard for Quality Test

10.2.1. Sampling Plan:

GB2828.1-2012

Single sampling, general inspection level II

10.2.2. Sampling Criteria:

Visual inspection: AQL 1.5

Electrical functional: AQL 0.65.

10.2.3. Reliability Test:

Detailed requirement refer to Reliability Test Specification.

10.3.Nonconforming Analysis & Disposition

10.3.1. Nonconforming analysis:

10.3.1.1. Customer should provide overall information of non-conforming sample for their complaints.

10.3.1.2. After receipt of detailed information from customer, the analysis of nonconforming parts usually should be finished in one week.

10.3.1.3. If cannot finish the analysis on time, customer will be notified with the progress status.

10.3.2. Disposition of nonconforming:

10.3.2.1. Non-conforming product over PPM level will be replaced.

10.3.2.2. The cause of non-conformance will be analyzed. Corrective action will be discussed and implemented.

10.4.Agreement Items

Shall negotiate with customer if the following situation occurs:

10.4.1. There is any discrepancy in standard of quality assurance.

10.4.2. Additional requirement to be added in product specification.

10.4.3. Any other special problem.


10.5. Standard of the Product Visual Inspection

10.5.1. Appearance inspection:

10.5.1.1. The inspection must be under illumination about 1000 – 1500 lx, and the distance of view must be at 30cm ± 2cm.

10.5.1.2. The viewing angle should be 45° from the vertical line without reflection light or follows customer's viewing angle specifications.

10.5.1.3. Definition of area: A Zone: Active Area, B Zone: Viewing Area,





10.5.2. Basic principle:


10.5.2.1. A set of sample to indicate the limit of acceptable quality level must be discussed by both us and customer when there is any dispute happened.





10.5.2.2. New item must be added on time when it is necessary.


10.6. Inspection Specification

| No. | Item | Criteria (Unit: mm) | | | | | | | | | | | | | | | | | | | | |
|-------------------------|---|---|------------|--------------|----------|------------------|-------|--------|-------------------------|-------|------------|---------------|--|-------|-----------|-------|--|-------|------|------------------------------------|--|--------|
| 01 | Black / White spot Foreign material (Round type) Pinholes Stain Particles inside cell. (Minor defect) | <div style="display: flex; align-items: center;"> <table border="1" style="border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Size</th> <th style="text-align: left;">Area</th> <th style="text-align: left;">Acc. Qty</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">$\phi \leq 0.20$</td> <td></td> <td style="text-align: center;">Ignore</td> </tr> <tr> <td style="text-align: center;">$0.20 < \phi \leq 0.50$</td> <td></td> <td style="text-align: center;">$N \leq 3$</td> </tr> <tr> <td style="text-align: center;">$0.50 < \phi$</td> <td></td> <td style="text-align: center;">0</td> </tr> </tbody> </table> </div> <p style="margin-top: 10px;">$\phi = (a + b) / 2$ Distance between 2 defects should more than 5mm apart.</p> | Size | Area | Acc. Qty | $\phi \leq 0.20$ | | Ignore | $0.20 < \phi \leq 0.50$ | | $N \leq 3$ | $0.50 < \phi$ | | 0 | | | | | | | | |
| Size | Area | Acc. Qty | | | | | | | | | | | | | | | | | | | | |
| $\phi \leq 0.20$ | | Ignore | | | | | | | | | | | | | | | | | | | | |
| $0.20 < \phi \leq 0.50$ | | $N \leq 3$ | | | | | | | | | | | | | | | | | | | | |
| $0.50 < \phi$ | | 0 | | | | | | | | | | | | | | | | | | | | |
| 02 | Electrical Defect (Minor defect) | <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th rowspan="2">Bright dot</th> <th colspan="2">Display Area</th> <th rowspan="2">Total</th> <th rowspan="4" style="font-size: small;">Note1</th> </tr> <tr> <th colspan="2">N ≤ 2</th> <th>N ≤ 2</th> </tr> </thead> <tbody> <tr> <th>Dark dot</th> <th colspan="2">N ≤ 4</th> <th>N ≤ 4</th> </tr> <tr> <th>Total dot</th> <th colspan="2">N ≤ 4</th> <th>N ≤ 4</th> </tr> <tr> <th>Mura</th> <th colspan="2">Not visible through 5% ND filters.</th> <th>Note 2</th> </tr> </tbody> </table> <p style="margin-top: 10px;">Remark: 1. Bright dot caused by scratch and foreign object accords to item 1.</p> | Bright dot | Display Area | | Total | Note1 | N ≤ 2 | | N ≤ 2 | Dark dot | N ≤ 4 | | N ≤ 4 | Total dot | N ≤ 4 | | N ≤ 4 | Mura | Not visible through 5% ND filters. | | Note 2 |
| Bright dot | Display Area | | | Total | Note1 | | | | | | | | | | | | | | | | | |
| | N ≤ 2 | | N ≤ 2 | | | | | | | | | | | | | | | | | | | |
| Dark dot | N ≤ 4 | | N ≤ 4 | | | | | | | | | | | | | | | | | | | |
| Total dot | N ≤ 4 | | N ≤ 4 | | | | | | | | | | | | | | | | | | | |
| Mura | Not visible through 5% ND filters. | | Note 2 | | | | | | | | | | | | | | | | | | | |

| 03 | <p>Black and White line Scratch Foreign material (Line type) (Minor defect)</p> |  <table border="1" data-bbox="555 719 1182 983"> <thead> <tr> <th>Length</th> <th>Width</th> <th>Acc. Qty</th> </tr> </thead> <tbody> <tr> <td>/</td> <td>$W \leq 0.1$</td> <td>Ignore</td> </tr> <tr> <td>$L \leq 2.5$</td> <td>$0.1 < W \leq 0.2$</td> <td>3</td> </tr> <tr> <td>$L > 2.5$</td> <td>$0.2 < W$</td> <td>0</td> </tr> <tr> <td colspan="2">Total</td> <td>3</td> </tr> </tbody> </table> <p>Distance between 2 defects should more than 3mm apart. Scratches not viewable through the back of the display are acceptable.</p> | Length | Width | Acc. Qty | / | $W \leq 0.1$ | Ignore | $L \leq 2.5$ | $0.1 < W \leq 0.2$ | 3 | $L > 2.5$ | $0.2 < W$ | 0 | Total | | 3 |
|--------------|---|---|--------|-------|----------|---|--------------|--------|--------------|--------------------|---|-----------|-----------|---|-------|--|---|
| Length | Width | Acc. Qty | | | | | | | | | | | | | | | |
| / | $W \leq 0.1$ | Ignore | | | | | | | | | | | | | | | |
| $L \leq 2.5$ | $0.1 < W \leq 0.2$ | 3 | | | | | | | | | | | | | | | |
| $L > 2.5$ | $0.2 < W$ | 0 | | | | | | | | | | | | | | | |
| Total | | 3 | | | | | | | | | | | | | | | |
| 04 | <p>Glass Crack (Minor defect)</p> |  <p>Crack is potential to enlarge, any type is not allowed.</p> | | | | | | | | | | | | | | | |

| 05 | <p>Glass Chipping Pad Area: (Minor defect)</p>  | <table border="1" data-bbox="858 1635 1329 1809"> <thead> <tr> <th>Length and Width</th> <th>Acc. Qty</th> </tr> </thead> <tbody> <tr> <td>$c > 3.0, b < 1.0$</td> <td>1</td> </tr> <tr> <td>$c < 3.0, b < 1.0$</td> <td>3</td> </tr> <tr> <td colspan="2">$a < \text{Glass Thickness}$</td> </tr> </tbody> </table> | Length and Width | Acc. Qty | $c > 3.0, b < 1.0$ | 1 | $c < 3.0, b < 1.0$ | 3 | $a < \text{Glass Thickness}$ | |
|------------------------------|--|--|------------------|----------|--------------------|---|--------------------|---|------------------------------|--|
| Length and Width | Acc. Qty | | | | | | | | | |
| $c > 3.0, b < 1.0$ | 1 | | | | | | | | | |
| $c < 3.0, b < 1.0$ | 3 | | | | | | | | | |
| $a < \text{Glass Thickness}$ | | | | | | | | | | |

| <p>06</p> | <p>Glass Chipping Rear of Pad Area: (Minor defect)</p>  | <table border="1"> <thead> <tr> <th>Length and Width</th> <th>Acc. Qty</th> </tr> </thead> <tbody> <tr> <td>$c > 3.0, b < 1.0$</td> <td>1</td> </tr> <tr> <td>$c < 3.0, b < 1.0$</td> <td>2</td> </tr> <tr> <td>$c < 3.0, b < 0.5$</td> <td>4</td> </tr> <tr> <td colspan="2">$a < \text{Glass Thickness}$</td> </tr> </tbody> </table> | Length and Width | Acc. Qty | $c > 3.0, b < 1.0$ | 1 | $c < 3.0, b < 1.0$ | 2 | $c < 3.0, b < 0.5$ | 4 | $a < \text{Glass Thickness}$ | |
|------------------------------|--|--|------------------|----------|--------------------|--------|------------------------------|---|--------------------|---|------------------------------|--|
| Length and Width | Acc. Qty | | | | | | | | | | | |
| $c > 3.0, b < 1.0$ | 1 | | | | | | | | | | | |
| $c < 3.0, b < 1.0$ | 2 | | | | | | | | | | | |
| $c < 3.0, b < 0.5$ | 4 | | | | | | | | | | | |
| $a < \text{Glass Thickness}$ | | | | | | | | | | | | |
| <p>07</p> | <p>Glass Chipping Except Pad Area: (Minor defect)</p>  | <table border="1"> <thead> <tr> <th>Length and Width</th> <th>Acc. Qty</th> </tr> </thead> <tbody> <tr> <td>$c > 3.0, b < 1.0$</td> <td>1</td> </tr> <tr> <td>$c < 3.0, b < 1.0$</td> <td>2</td> </tr> <tr> <td>$c < 3.0, b < 0.5$</td> <td>4</td> </tr> <tr> <td colspan="2">$a < \text{Glass Thickness}$</td> </tr> </tbody> </table> | Length and Width | Acc. Qty | $c > 3.0, b < 1.0$ | 1 | $c < 3.0, b < 1.0$ | 2 | $c < 3.0, b < 0.5$ | 4 | $a < \text{Glass Thickness}$ | |
| Length and Width | Acc. Qty | | | | | | | | | | | |
| $c > 3.0, b < 1.0$ | 1 | | | | | | | | | | | |
| $c < 3.0, b < 1.0$ | 2 | | | | | | | | | | | |
| $c < 3.0, b < 0.5$ | 4 | | | | | | | | | | | |
| $a < \text{Glass Thickness}$ | | | | | | | | | | | | |
| <p>08</p> | <p>Glass Corner Chipping: (Minor defect)</p>  | <table border="1"> <thead> <tr> <th>Length and Width</th> <th>Acc. Qty</th> </tr> </thead> <tbody> <tr> <td>$c < 3.0, b < 3.0$</td> <td>Ignore</td> </tr> <tr> <td colspan="2">$a < \text{Glass Thickness}$</td> </tr> </tbody> </table> | Length and Width | Acc. Qty | $c < 3.0, b < 3.0$ | Ignore | $a < \text{Glass Thickness}$ | | | | | |
| Length and Width | Acc. Qty | | | | | | | | | | | |
| $c < 3.0, b < 3.0$ | Ignore | | | | | | | | | | | |
| $a < \text{Glass Thickness}$ | | | | | | | | | | | | |
| <p>09</p> | <p>Glass Burr: (Minor defect)</p>  | <table border="1"> <thead> <tr> <th>Length</th> <th>Acc. Qty</th> </tr> </thead> <tbody> <tr> <td>$F < 1.0$</td> <td>Ignore</td> </tr> </tbody> </table> <p>Glass burr don't affect assemble and module dimension.</p> | Length | Acc. Qty | $F < 1.0$ | Ignore | | | | | | |
| Length | Acc. Qty | | | | | | | | | | | |
| $F < 1.0$ | Ignore | | | | | | | | | | | |

| 10 | <p>FPC Defect: (Minor defect)</p>  | <p>10.1 Dent, pinhole width $a < w/3$. (w: circuitry width.)</p> <p>10.2 Open circuit is unacceptable.</p> <p>10.3 No oxidation, contamination and distortion.</p> | | | | | | | | |
|----------------------------|---|--|----------|----------|---------------------|--------|----------------------------|------------|------------------|---------|
| 11 | <p>Bubble on Polarizer (Minor defect)</p> | <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th style="padding: 5px;">Diameter</th> <th style="padding: 5px;">Acc. Qty</th> </tr> </thead> <tbody> <tr> <td style="padding: 5px;">$\varphi \leq 0.30$</td> <td style="padding: 5px;">Ignore</td> </tr> <tr> <td style="padding: 5px;">$0.30 < \varphi \leq 0.50$</td> <td style="padding: 5px;">$N \leq 2$</td> </tr> <tr> <td style="padding: 5px;">$0.50 < \varphi$</td> <td style="padding: 5px;">$N = 0$</td> </tr> </tbody> </table> | Diameter | Acc. Qty | $\varphi \leq 0.30$ | Ignore | $0.30 < \varphi \leq 0.50$ | $N \leq 2$ | $0.50 < \varphi$ | $N = 0$ |
| Diameter | Acc. Qty | | | | | | | | | |
| $\varphi \leq 0.30$ | Ignore | | | | | | | | | |
| $0.30 < \varphi \leq 0.50$ | $N \leq 2$ | | | | | | | | | |
| $0.50 < \varphi$ | $N = 0$ | | | | | | | | | |
| 12 | <p>Dent on Polarizer (Minor defect)</p> | <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th style="padding: 5px;">Diameter</th> <th style="padding: 5px;">Acc. Qty</th> </tr> </thead> <tbody> <tr> <td style="padding: 5px;">$\varphi \leq 0.25$</td> <td style="padding: 5px;">Ignore</td> </tr> <tr> <td style="padding: 5px;">$0.25 < \varphi \leq 0.50$</td> <td style="padding: 5px;">$N \leq 4$</td> </tr> <tr> <td style="padding: 5px;">$0.50 < \varphi$</td> <td style="padding: 5px;">None</td> </tr> </tbody> </table> | Diameter | Acc. Qty | $\varphi \leq 0.25$ | Ignore | $0.25 < \varphi \leq 0.50$ | $N \leq 4$ | $0.50 < \varphi$ | None |
| Diameter | Acc. Qty | | | | | | | | | |
| $\varphi \leq 0.25$ | Ignore | | | | | | | | | |
| $0.25 < \varphi \leq 0.50$ | $N \leq 4$ | | | | | | | | | |
| $0.50 < \varphi$ | None | | | | | | | | | |
| 13 | <p>Bezel</p> | <p>13.1 No rust, distortion on the Bezel.</p> <p>13.2 No visible fingerprints, stains or other contamination.</p> | | | | | | | | |
| 14 | <p>Touch Panel</p> | <p>D: Diameter W: width L: length</p> <p>14.1 Spot: $D < 0.25$ is acceptable $0.25 \leq D \leq 0.4$</p> <p>2dots are acceptable and the distance between defects should more than 10 mm.</p> <p>$D > 0.4$ is unacceptable</p> <p>14.2 Dent: $D > 0.40$ is unacceptable</p> <p>14.3 Scratch: $W \leq 0.03$, $L \leq 10$ is acceptable, $0.03 < W \leq 0.10$, $L \leq 10$ is acceptable</p> <p>Distance between 2 defects should more than 10 mm.</p> <p>$W > 0.10$ is unacceptable.</p> | | | | | | | | |
| 15 | <p>PCB</p> | <p>15.1 No distortion or contamination on PCB terminals.</p> <p>15.2 All components on PCB must same as documented on the BOM/component layout.</p> <p>15.3 Follow IPC-A-600F.</p> | | | | | | | | |
| 16 | <p>Soldering</p> | <p>Follow IPC-A-610C standard</p> | | | | | | | | |
| 17 | <p>Electrical Defect (Major defect)</p> | <p>The below defects must be rejected.</p> <p>17.1 Missing vertical / horizontal segment,</p> | | | | | | | | |

| | | |
|--|--|---|
| | | <p>17.2 Abnormal Display.</p> <p>17.3 No function or no display.</p> <p>17.4 Current exceeds product specifications.</p> <p>17.5 LCD viewing angle defect.</p> <p>17.6 No Backlight.</p> <p>17.7 Dark Backlight.</p> <p>17.8 Touch Panel no function.</p> |
|--|--|---|

Remark: LCD Panel Broken shall be rejected. Defect out of LCD viewing area is acceptable.

10.7. Classification of Defects

- 10.7.1. Visual defects (Except no / wrong label) are treated as minor defect and electrical defect is major.
- 10.7.2. Two minor defects are equal to one major in lot sampling inspection.


10.8. Identification/marketing criteria

Any unit with illegible / wrong / double or no marking/ label shall be rejected.

10.9. Packing

- 10.9.1. There should be no damage of the outside carton box, each packaging box should have one identical label.
- 10.9.2. Modules inside package box should have compliant mark.
- 10.9.3. All direct package materials shall offer ESD protection.

Note1: Bright dot is defined as the defective area of the dot is larger than 50% of one sub-pixel area.



Bright dot: The bright dot size defect at black display pattern. It can be recognized by 2% transparency of filter when the distance between eyes and panel is $350\text{mm} \pm 50\text{mm}$.

Dark dot: Cyan, Magenta or Yellow dot size defect at white display pattern. It can be recognized by 5% transparency of filter when the distance between eyes and panel is $350\text{mm} \pm 50\text{mm}$.

Note2: Mura on display which appears darker / brighter against background brightness on parts of display area.

11. Reliability Specification

| No | Item | Condition | Quantity | Criteria |
|----|-----------------------------|---|----------|------------------|
| 1 | High Temperature Operating | 70°C, 96Hrs | 2 | GB/T2423.2-2008 |
| 2 | Low Temperature Operating | -20°C, 96Hrs | 2 | GB/T2423.1-2008 |
| 3 | High Humidity | 50°C, 90%RH, 96Hrs | 2 | GB/T2423.3-2016 |
| 4 | High Temperature Storage | 80°C, 96Hrs | 2 | GB/T2423.2-2008 |
| 5 | Low Temperature Storage | -30°C, 96Hrs | 2 | GB/T2423.1-2008 |
| 6 | Thermal Cycling Test | -20°C, 60min~70°C, 60min, 20 cycles. | 2 | GB/T2423.22-2012 |
| 7 | Packing vibration | Frequency range:10Hz~50Hz Acceleration of gravity:5G X, Y, Z 30 min for each direction. | 2 | GB/T5170.14-2009 |
| 8 | Electrical Static Discharge | Air: $\pm 8KV$ 150pF/330 Ω 5 times Contact: $\pm 4KV$ 150pF/330 Ω 5 times | 2 | GB/T17626.2-2018 |
| 9 | Drop Test (Packaged) | Height:80 cm,1 corner, 3 edges, 6 surfaces. | 2 | GB/T2423.8-1995 |

Note1. No deflection cosmetic and operational function allowable.

Note2. Total current Consumption should be below double of initial value

12. Precautions and Warranty

12.1. Safety

- 12.1.1. The liquid crystal in the LCD is poisonous. Do not put it in your mouth. If the liquid crystal touches your skin or clothes, wash it off immediately using soap and water.
- 12.1.2. Since the liquid crystal cells are made of glass, do not apply strong impact on them. Handle with care.

12.2. Handling

- 12.2.1. Reverse and use within ratings in order to keep performance and prevent damage.
- 12.2.2. Do not wipe the polarizer with dry cloth, as it might cause scratch. If the surface of the LCD needs to be cleaned, wipe it swiftly with cotton or other soft cloth soaked with petroleum IPA, do not use other chemicals.

12.3. Storage

- 12.3.1. Do not store the LCD module beyond the specified temperature ranges.
- 12.3.2. Strong light exposure causes degradation of polarizer and color filter.

12.4. Metal Pin (Apply to Products with Metal Pins)

12.4.1. Pins of LCD and Backlight

12.4.1.1. Solder tip can touch and press on the tip of Pin LEAD during the soldering

12.4.1.2. Recommended Soldering Conditions

Solder Type: Sn96.3~94-Ag3.3~4.3-Cu0.4~1.1



Maximum Solder Temperature: 370°C

Maximum Solder Time: 3s at the maximum temperature

Recommended Soldering Temp: 350±20°C

Typical Soldering Time: ≤3s

12.4.1.3. Solder Wetting



12.4.2. Pins of EL

12.4.2.1. Solder tip can touch and press on the tip of EL leads during soldering.

12.4.2.2. No Solder Paste on the soldering pad on the motherboard is recommended.

12.4.2.3. Recommended Soldering Conditions

Solder type: Nippon Alimit Leadfree SR-34, size 0.5mm

Recommended Solder Temperature: 270~290°C


Typical Soldering Time: ≤2s

Minimum solder distance from EL lamp (body):2.0mm


12.4.2.4. No horizontal press on the EL leads during soldering.

12.4.2.5. 180° bend EL leads three times is not allowed.

12.4.2.6. Solder Wetting




Recommended




Not Recommended

12.4.2.7. The type of the solder iron:




Recommended



Not Recommended

12.4.2.8. Solder Pad



12.5.Operation

- 12.5.1. Do not drive LCD with DC voltage
- 12.5.2. Response time will increase below lower temperature
- 12.5.3. Display may change color with different temperature
- 12.5.4. Mechanical disturbance during operation, such as pressing on the display area, may cause the segments to appear "fractured".
- 12.5.5. Do not connect or disconnect the LCM to or from the system when power is on.
- 12.5.6. Never use the LCM under abnormal condition of high temperature and high humidity.
- 12.5.7. Module has high frequency circuits. Sufficient suppression to the electromagnetic interface shall be done by system manufacturers. Grounding and shielding methods may be important to minimize the interference.
- 12.5.8. Do not display the fixed pattern for long time (we suggest the time not longer than half of one hour) because it may develop image sticking due to the TFT structure.

12.6.Static Electricity

- 12.6.1. CMOS LSIs are equipped in this unit, so care must be taken to avoid the electro-static charge, by ground human body, etc.
- 12.6.2. The normal static prevention measures should be observed for work clothes and benches.
- 12.6.3. The module should be kept into anti-static bags or other containers resistant to static for storage.

12.7.Limited Warranty

- 12.7.1. Our warranty liability is limited to repair and/or replacement. We will not be responsible for any consequential loss.
- 12.7.2. If possible, we suggest customer to use up all modules in six months. If the module storage time over twelve months, we suggest that recheck it before the module be used.
- 12.7.3. After the product shipped, any product quality issues must be feedback within three months, otherwise, we will not be responsible for the subsequent or consequential events.

13. Packaging

TBD

